

60 SERIES HC60W45R2P-V



5MP AI Outdoor Dome Camera



Honeywell's new and improved Honeywell 60 Series 5MP AI outdoor dome cameras offer exceptional performance in variable (bright sunshine and shadows) and low light conditions with enhanced video/object analytics to highlight intricate details of persons, objects and vehicles. These cameras also feature the latest FIPS 140-3 encryption standard as well as increased local storage (up to 1 TB) making them ideal for larger enterprise applications where cybersecurity and regulatory compliance is essential.

ENHANCED DETECTION AND IMAGING

- Upgraded WDR (up to 140 dB) to significantly reduce image glare
- Increased IR distance (up to 60 m (197 ft))
- P-Iris and improved minimum illumination (0.007 Lux@30 IRE) provides better image quality in variable or low light conditions
- Improved shutter speed (1/100000 ~ 1/5) allows faster capture of moving subjects, reducing motion blur and producing sharper images
- Enhanced 3D noise reduction eliminates visual noise resulting in crisper details for identifying objects or people in video footage
- Smart IR Technology automatically adjusts to changing light conditions and object distances for better capture of details even in dimly lit or nighttime scenes

INTELLIGENT SURVEILLANCE

- New and improved probabilistic AI video object analytics to quickly detect suspicious activities and identify attributes such as faces, vehicles, gender, age, colors of cars or personal attire for faster investigative search
- Visible bounding boxes with MAXPRO integration
- Supported in the Milestone plugin intelligent search

INCREASED OPERATIONAL EFFICIENCY

- System security enhancements with Secure Boot and latest FIPS 140-3 chipset provide secure data integrity and privacy
- Upgraded local storage (up to 1 TB) or 4X the amount of previous models significantly boosts camera data management and retention capacity
- ONVIF Profile M allows analytics metadata and events to be securely and seamlessly integrated within video surveillance systems for better operational decision making
- Built-in PoE eliminates need for separate power supply and associated wiring
- Remote configuration, motorized zoom adjustments and auto-focus can be performed from web client or NVR

RUGGED, FLEXIBLE, COMPLIANT

- Built for challenging environments (IP66, IP67, NEMA 4X, TS-2, IK10)
- Flexible wall or ceiling mount options - inside or outside
- NDAA and NIS2 compliant

POTENTIAL APPLICATIONS:

- Entrances, Lobbies
- Receiving / Loading Docks
- Outdoor Public Areas / Grounds / Campuses / Plazas
- Passenger Terminals / Operations / Maintenance Areas
- Parking Lots / Garages

INDUSTRIES:

- Large Office Buildings
- Manufacturing / Logistics / Warehouses
- Hospitals / Healthcare Facilities
- Schools / Universities
- Stadiums / Event Venues
- Hotels / Hospitality
- Gaming / Casinos
- Airports / Train Stations / Bus Terminals
- Banking
- Datacenters
- Pharma
- Government/Military Installations
- Retail (Big Box)

Honeywell

60 SERIES 5MP AI OUTDOOR DOME CAMERA

OPERATIONAL	
RAM	2 Gigabytes
Flash	16 Gigabytes
Video Standard	NTSC / PAL
Scanning System	Progressive
Image Sensor	Sony STARVIS 2 IMX675, 1/2.8" CMOS
Sensor size (H x V)	5.184 x 3.888 mm
Number Of Pixels (H x V)	5MP (2592 x 1944)
Min. Illumination (Color/B/W)	Color: 0.007 Lux@30IRE F1.4 B/W: 0Lux @F1.4(IR on)
S/N Ratio	55 dB
Electronic Shutter Speed	1/5 ~ 1/100000 s
IR Distance	Up to 60 m (197 ft)
IR Light Control	Smart IR (Auto / Manual) / OFF
IR Light Number	4
Removable IR-Cut Filter	Yes
Day/Night	Auto / Day Mode / Night Mode / Timing
Backlight Compensation	WDR, HLC, BLC
White Balance	Auto / Tungsten / Fluorescent / Daylight / Shadow / Manual
Gain Control	0~100 %
Wide Dynamic Range	Up to 140 dB
Noise Reduction	2D / 3D DNR
Lens	2.7-13.5 mm, F1.4-F2.8, P-Iris
G-Sensor	Supported (hardware)
Electronic Image Stabilization	Supported
Angle Of View	H: 100° ~ 30°, V: 72° ~ 23
Privacy Masking	Off / On (4 Areas)
Defog	Supported
Encryption Chipset	Built-In FIPS 140-3 Encryption Chipset
Local Storage	Micro SD / SDHC / SDXC card slot (up to 1TB)
Micro USB	Support Wi-Fi Dongle for configuration
Alarm Inputs / Outputs	2 In / 1 Relay Out

VIDEO			
Video Compression		H.265 HEVC / H.264 / MJPEG, Smart Codec	
Resolution	PAL	NTSC	
	Stream 1 H.264/H.265: 2592 x 1944, 2688 x 1520, 2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720 @25 fps 2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720@50 fps MJPEG: 1920 x 1080, 1280 x 720 @12 fps Stream 2 2592 x 1944, 1920 x 1080, D1 (704 x 576), VGA (640 x 480), CIF (352 x 288)@25 fps 2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720, D1 (704 x 576), VGA (640 x 480), CIF (352 x 288)@50 fps MJPEG: 1920 x 1080, D1 (704 x 576), VGA (640 x 480), CIF (352 x 288) @12 fps Stream 3 H.264/H.265: 2592 x 1944, VGA (640 x 480), CIF (352 x 288), QVGA (320 x 240) @25 fps 1920 x 1080, 1280 x 720, VGA (640 x 480), CIF (352 x 288), QVGA (320 x 240) @50 fps MJPEG: VGA (640 x 480), CIF (352 x 288), QVGA (320 x 240) @12 fps MJPEG: 1920 x 1080, 1280 x 720, VGA (640 x 480), CIF (352 x 288), QVGA (320 x 240) @12 fps	Stream 1 H.264/H.265: 2592 x 1944, 2688 x 1520, 2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720 @30 fps 2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720@60 fps MJPEG: 1920 x 1080, 1280 x 720 @12 fps Stream 2 2592 x 1944, 1920 x 1080, D1 (704 x 480), VGA (640 x 480), CIF (352 x 240)@30 fps 2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720, D1 (704 x 480), VGA (640 x 480), CIF (352 x 240)@60 fps MJPEG: 1920 x 1080, D1 (704 x 480), VGA (640 x 480), CIF (352 x 240) @12 fps Stream 3 H.264/H.265: 2592 x 1944, VGA (640 x 480), CIF (352 x 240), QVGA (320 x 240) @30 fps 1920 x 1080, 1280 x 720, VGA (640 x 480), CIF (352 x 240), QVGA (320 x 240), QVGA (320 x 240) @60 fps MJPEG: VGA (640 x 480), CIF (352 x 240), QVGA (320 x 240) @12 fps MJPEG: 1920 x 1080, 1280 x 720, VGA (640 x 480), CIF (352 x 240), QVGA (320 x 240)@12 fps	
	Number of Video Streams	3	
	Frame Rate	Stream1: MAX 25/30 fps 2592 x 1944, 2688 x 1520, 2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720 MAX 50/60 fps 2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720 Stream2: MAX 25 fps 2592 x 1944, 1920 x 1080, 704 x 576, 640 x 480, 352 x 288 MAX 30 fps 2592 x 1944, 1920 x 1080, 704 x 480, 640 x 480, 352 x 240 MAX 50 fps 2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720, 704 x 576, 640 x 480, 352 x 288 MAX 60 fps 2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720, 704 x 480, 640 x 480, 352 x 240 Stream3: MAX 25 fps 2592 x 1944,640 x 480, 352 x 288, 320 x 240 MAX 30 fps 2592 x 1944, 640 x 480, 352 x 240, 320 x 240 MAX 50 fps 1920 x 1080, 1280 x 720, 640 x 480, 352 x 288, 320 x 240 MAX 60 fps 1920 x 1080, 1280 x 720, 640 x 480, 352 x 240, 320 x 240	
Bit Rate	100kbps ~ 16000kbps		
AUDIO			
Audio Compression	G.711a / G.711 Mu / G.726		
Audio Stream	Full duplex, simplex		
Audio Interface	Line In / Out		

60 SERIES 5MP AI OUTDOOR DOME CAMERA


NETWORK		MECHANICAL	
Ethernet	10 Base-T / 100 Base-TX Ethernet (RJ-45)	Dimensions (Ø x H)	Ø 159.0 x 109.8 mm (Ø 6.26" x 4.32")
Supported Web Browsers	Microsoft Edge, Chrome	Dome diameter	96.4 mm (3.80")
Supported OS	Microsoft Windows 10, Windows 11	Package Dimensions (D x D x H)	195 x 195 x 185 mm (7.68" x 7.68" x 7.28")
Protocols*	IPv4, IPv6, TCP / IP, HTTP, HTTPS, RTSP / RTP / RTCP, IGMP / Multicast, SMTP, DHCP, NTP, DNS, QoS, SNMP, 802.1X, UDP, ICMP, ARP, TLS, FTP/SFTP, DDNS	Product Weight	0.96 kg (2.12 lb)
Interoperability	ONVIF Profile S, G, T, M	Package Weight	1.51 kg (3.33 lb)
Maximum Users Access	10 Users	Material	Metal (die casting aluminum with powder coating)
Security	User account and password protection, HTTPS, IP Filter, Digest authentication, TLS1.2&TLS1.3, Stream encryption, AES128 / 256, SSH / Telnet closed, PCI-DSS compliance, Built-In encryption chipset	Color	White (RAL9003)
Secure Boot	Supported	ENVIRONMENTAL	
Languages Supported	Arabic, Czech, Dutch, English, French, German, Italian, Japanese, Korean, Polish, Portuguese (Brazil), Spanish, Turkish, Traditional Chinese	Operating Temperature	Starting Temperature: -40°C ~ 60°C (-40°F ~ 140°F) Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F) (65° for 4 hours when IR off) Maximum temperature according to NEMA TS2 (para 2.8-2.9): 74 °C (165 °F)
EVENTS / ANALYTICS		Relative Humidity	Less than 95 %, non-condensing
Video Analytics	Motion Detection, Smart Motion, Scene Change, Intrusion, Multi Loitering, Face Detection, Line Crossing Detection, Unattended Object Detection, Missing Object Detection	Ingress Protection	IP66, IP67, NEMA 4X
Object Analytics	Object Classes: Humans, Vehicles	Impact Resistance	IK10
	Object Data: Vehicle: Car / Truck / Motorcycle / Bus Gender: Male / Female Face mask detection: with mask / without mask** Age: Young / Adult / Middle Age / Senior Colors of cars or personal clothing: Blue / Yellow / Black / White / Green/ Red / Gray / Purple / Pink / Brown /Teal/ Colorful / Beige / Gold / Orange / Silvery / Floral	Heater	Yes
		Gore-Vent	Yes
		Fan	Yes
Audio Analytics	Audio Classes: Glass Break, Scream, Gunshot, Loud Sound	REGULATORY	
Event Type	Alarm Input, SD Card Alarm, Abnormal Sound Alarm, Illegal Access Alarm	Emissions	FCC PART 15, ICES, CE (EN 55032), Complies with UKCA and RCM
Event Linkage	Event notification using digital output, FTP/SFTP, Email, Micro SD card recording and audio output	Immunity	CE(EN 50130-4, EN55035), Complies with UKCA and RCM
Region Of Interest	8	Safety	UL LISTED TO UL/CSA 62368-1, CE(EN 62368-1), Complies with UKCA and RCM
ELECTRICAL		RoHS	CE(EN 63000), UAE(Cabinet Decree No.10 of 2017)
Power Supply	AC24V, 1.5A, 50-60Hz; or DC12V=2.5A; or PoE 44-57V=, 350mA (IEEE 802.3af)	Country of Origin	Vietnam
Power Consumption	Max. 12.5 W	Warranty	5 years
DORI (EN62676-4 STANDARD)			
	Wide	Tele	
Detect	62 m (203.41ft)	215 m (705.38 ft)	
Observe	24.8 m (81.36 ft)	86 m (282.15 ft)	
Recognize	14.2 m (46.59 ft)	43 m (141.08 ft)	
Identify	6.2 m (20.34 ft)	21.5 m (70.54 ft)	

* Some development may be required in specific user cases to support some of these protocols in the field as they mature over time.

** Face mask detection is a beta feature.

60 SERIES 5MP AI OUTDOOR DOME CAMERA

DIMENSIONS



SYSTEM COMPATIBILITY & RECOMMENDED ACCESSORIES

SYSTEM COMPATIBILITY		OPTIONAL MOUNTS AND ACCESSORIES**	
MAXPRO NVR	Supported with MAXPRO R795	HA60JCBH2	60S dome junction box
ADPRO NVR iFT-E*	Up to 32 IP channels with up to 32 VA channels NVRs	HA35PLM01	35S pole mount bracket
ADPRO NVR iFT*	Up to 32 IP channels or 16 IP channels with up to 16 VA channels NVRs	HA35CNM01	35S corner mount bracket
ADPRO NVR eFT-S*	Up to 16 IP channels or 8 IP channels with up to 8 VA channels NVRs	HA60WLMB1	60S wall mount bracket, 1.5NPT female
Honeywell DVM*	Supported with Honeywell DVM R800	HA60WLM4F	60S wall mount bracket, with cap
35 Series NVR	4/8/16/32/64-channel 35 series NVRs	HA60PMC4FI	60S outdoor dome fisheye cap 3/4NPT female
Third Party Systems	Supported with Milestone 2025 R1	HA60PMC4FO	60S outdoor dome fisheye cap 1.5NPT male
		HA35CLM01	35S ceiling mount base with adapter
		HA35CLM02	35S ceiling mount pendent extension, 252mm
		HA60WIF	60S Wi-Fi dongle and USB adapter for camera configuration
		HA60CB4I	60S outdoor dome camera bubble replacement (clear) - for HC60W45R2P-V
		HA60SB4I	60S outdoor dome camera bubble replacement (smoke) - for HC60W45R2P-V
		HA60APR	60S outdoor dome adapter plate and rubber

*Limited features are supported for compatibility. Please refer to the Integration Matrix for detailed information.

** Mounting accessories, unless otherwise noted, are not included with camera and must be ordered separately. Please refer to the cross reference matrix or accessories datasheet for detailed information.
HA60JCBH2 - coming in 2026
HA60APR is included in camera package

ORDERING

PART NUMBER	DESCRIPTION
HC60W45R2P-V	60 Series 5 MP AI Outdoor Dome Camera, WDR up to 140 dB, 1/2.8" CMOS, 2.7-13.5 mm MFZ, 4 IR LEDs, PoE, IP66/IP67/NEMA 4X/TS-2/IK10



For more information

buildings.honeywell.com/security

Honeywell Commercial Security

715 Peachtree St. NE

Atlanta, GA 30308

1.800.323.4576

www.honeywell.com

ONVIF and the ONVIF logo are trademarks of ONVIF Inc.
HEVC Advance logo is a trademark of HEVC Advance.
Sony and Sony STARVIS are registered trademarks of Sony Corporation.

Honeywell reserves the right, without notification, to make changes in product design or specifications.

HBA-SEC-60S-HC60W45R2P-V-DS-US-EN-09-2025-V01-Y
© 2025 Honeywell International Inc.

Honeywell