





## **Dimensions** Unit: Inch (mm) 9.84 11.81 (250.1mm) (300mm) (45mm)

## Summary

COVA is DW's gateway appliance to cloud-managed services. It is an easy-to-use recording solution for myDW subscribers, combining cloud monitoring, health management and clip sharing with on-site storage — Optimized and Secure.

The COVA NVR is managed through myDW health monitoring services, with video recorded locally and live viewing, playback, event notifications and user management available through the COVA web client, myDW dashboard and DW Mobile+ App. The hardware has 4 built-in PoE ports with 25.5 watts power, supports recording at real-time 30fps at up to 4K (8MP) resolution, and up to 10TB storage. It is protected by DW's and an unbeatable full 5-year warrantv.

## **Features**

- · Complete installation in minutes!
- · Setup and camera configuration via the DW Mobile Plus App. Skip the local monitor!
- Record and manage single-sensor IP cameras at real-time 30fps up to 4K, with 80Mbps maximum throughput
- 4GB myDW cloud storage for Clip Share included
- Includes 12 months subscription to myDW services
- Local power for up to 4 IP cameras via resident PoE switch makes the installation seamless and efficient.
- Remote user and event management via myDW health monitoring services.
- Upload events to myDW via Clip Share to address critical events quickly and efficiently.
- Up to 10TB local storage
- Compatible with ONVIF cameras
- · Live, playback and video archiving via the web client
- · Static and dynamic live camera views
- Event notifications and system health reports via myDW
- IdentiSee enables the search of individuals and vehicles that AI cameras have detected.
- Audio communications from supported IP cameras
- NDAA-compliant for federal and government projects
- 5 year warranty

## **Specifications**

VIDEO	rctom	Embedded Linux
Operating sy		
System	Channels	4 channels
	Number of PoE ports	4 PoE ports
	Supported camera	Up to 8MP
	resolutions	True HD, VGA
Display	Video output ports	True HD: 3840 x 2160 / 1920 x 1080 / 1280 x 1024/
	Video output resolution	1024 x 768
		VGA: 1920 x 1080 / 1280 x 1024/1024 x 768
	Disalerrased	Real-time 30fps live display per channel.
	Display speed	
	Screen display mode	1, 4
Ports	System operations	USB mouse
	USB	USB 2.0 x 2
	FORMANCE	
Recording resolution		Up to 8MP
Recording speed		Up to 30fps per channel in any resolution
Maximum throughput		80 Mpbs
Recording modes		Schedule, continuous, event
Decoding	Live view and playback	Up to 30fps
Audio Storage	Network input	4-channels input from supported IP cameras
	Local input/output	Disabled
	Compression	G.711(U/A)
	HDD interface	1x SATA HDD
	Maximum internal storage	
NETWORK	PERFORMANCE	-   -   -   -   -   -   -   -   -   -
LAN		10/100/1000Mbps Ethernet (JR45)
Compression		H.265 / H.264
Protocol		TCP / IP, IPv4, IPv6, UDP, DHCP, DNS, DDNS,
		UPnP, NTP, HTTP, SMTP, 802.1x, RTSP, RTP, RTCP,
FIOLOCOI		WebSocket, ONVIF
		Live monitoring, remote playback and file backup
	Remote web client features	Playback up to 4 channels, 30fps per channel
		Timeline, calendar (date and time), event search,
		Identisee
Access		Remote system reboot, FW updates, system
		management and remote PTZ control
		Cloud-Base Health Monitoring
	myDW camera health monitoring	User management, events and system health
		notifications, video share and cloud upload
		Remote system reboot, FW updates and system
		management
	Max stream connections	up to 16CH, Playback: up to 4CH
Remote time		Time synchronization to an NTP server (pool.ntp.org)
	very after power failure	Auto-reboot and journaling file system
	, arter power failure	Over the network, video share via myDW cloud-base
Backup		VMS
GENERAL		
Operating to	mperature	14 ~ 122°F (-10 ~ 50°C)
Operating humidity		10% ~ 90% humidity
System	Power requirements	DC 48V/1.25A
	Power requirements  Power consumption	Up to 10W ( without HDD )
	· ·	
PoE	PoE ports	100M RJ45 x 4
	Standards	IEEE802.3AF/AT
	Maximum power per port	i
Output power		Up to 48W
Dimensions (WxDxH)		11.81" x 9.8" x 1.77" (300 x 250.1 x 45mm)
Certificate		CE, FCC, NDAA, RoHS
Warranty		5 year warranty











