

See Farther & Wider.

SECURITY CAMERAS
The First Name in Security

High image-quality monitoring with optical performance supporting 3 megapixels. Advanced design engineering and special optic glass adopted, best suited for color, Black & White, and Day and Night cameras. SLA-F-M1550DN has an f15-50mm, 3.3x zooming application compatible lens. Lens SLA-F-M226DN is equipped with a wide 2.2mm, achieving a horizontal field angle of 144 degrees (when used on 1/2.7" sensor cameras) Both lenses are designed to maximize optical performance with high-accuracy aspheric lens, low-dispersion glass, and high refractiveindex glass. Built-in ND filter of T360, supporting high sensitivity cameras.



3 Megapixel Day/Night Varifocal 1/2.7"

- F2.2-6mm / F1.3: SLA-F-M226DN
- f15-50mm / F1.5: SLA-F-M1550DN
- · 3 Megapixel Resolution
- · Auto Iris (DC type)
- · Day & Night
- ND Filter
- Aspherical Lens
- · RoHS Compliant



SLA-F-M1550DN SLA-F-M226DN



Specifications





	SLA-F-M1550DN	SLA-F-M226DN
Description	3 Megapixel Resolution	3 Megapixel Resolution
	Day & Night Lens	Day & Night Lens
Focal length	15mm ~ 50mm	2.2mm ~ 6mm
Zoom factor	3.3	2.7
Applicable lens	for 1/2.7" ~ 1/4" cameras	for 1/2.7" ~ 1/4" cameras
Iris range	F1.5~T360 (Equivalent to F360)	F1.3~T360 (Equivalent to F360)
Operation iris	Auto (DC Type)	Auto (DC Type)
Operation zoom	Manual	Manual
Operation focus	Manual	Manual
Angle of view	1/2.7"	1/2.7"
	Wide: 20° 01' x 15° 05'	Wide: 144°17' × 82°13'
	Tele: 06° 09' x 04° 39'	Tele: 54°53' × 31°01'
	1/3"	1/3"
	Wide: 18° 14' x 13° 43'	Wide: 131°34' × 74°46'
	Tele: 05° 37' x 04° 14'	Tele: 49°55' × 28°11'
Minimum object distance (M.O.D.)	1 meter (3.28 feet)	0.3 meter (0.98 foot)
Focusing range (from front lens)	infinity ~ 1 meter (3.28 feet)	infinity ~ 0.3 meter (0.98 foot)
Mount	CS	CS
Mass in Weight	65g (0.143 lbs)	80g (0.176 lbs)



Design and specifications are subject to change without notice.



SAMSUNG TECHWIN AMERICA Inc. 100 Challenger Rd. Suite 700 Ridgefield Park, NJ 07660 Toll Free: +1-877-213-1222 Direct: +1-201-325-6920 Fax: +1-201-373-0124

