

2MP IR NETWORK BULLET CAMERA

PRO
SERIES



IPC-2MPSR300 – 2MP PRO-Series All Weather IR-300' Range 5-50mm Network Bullet Camera

PRO Series 2-MegaPixel ready, All-Weather Network Bullet Camera featuring an enhanced **5-50mm Varifocal zoom lens** with variable **infrared night vision up to 300 Feet**. Perfect for day & night surveillance applications including: Warehouses, Parking Lots, Shopping Centers, Gas Stations and other high-risk areas.

ADVANTAGES

- High-Definition H.264 **2-MegaPixels (1920 x 1080) @ 30fps**
- **High-Intensity Night-Vision IR Range up to 300 Feet**
- **Dynamic 5mm-50mm Varifocal Zoom Lens**
- Vandal-Resistant IP-66 Rated All-Weather Design
- ONVIF Compliant & PoE Ready for Easy Installation
- Includes License-Free 64 Channel Client Management Software
- Perfect for Warehouses, Parking Lots, Shopping Centers, Gas Stations and other High-Risk Areas
- 100% Performance Guarantee & World Class Technical Support



APPLICATIONS INCLUDE**SPECIFICATIONS**

CAMERA TYPE	1/2.5" Micron CMOS Sensor
RESOLUTION	Main Stream 2MP @ 30fps (1920 x 1080) Sub Stream 4CIF NTSC (704 x 480) PAL (704 x 576)
VIDEO FORMAT	NTSC / PAL
STANDARDS	ONVIF
CAMERA LENS TYPE	5-50mm Varifocal Zoom with 5.65°~53.2° Viewing Angle
CAMERA S/N RATIO	>60dB (Enhanced))
CAMERA SYNC / WHITE BALANCE	Automatic
CAMERA ELECTRONIC SHUTTER	1/50~1/10,000 Seconds
CAMERA IR RANGE	IR Array up to 300 Feet & 10,000+ Lifetime Hours (Made in Germany)
CAMERA MINIMUM ILLUMINATION	Color 0.6 Lux / B&W 0.08 Lux ~ (0.0 Lux IR ON)
CAMERA IR CUT FILTER	Automatic / Mechanical
VIDEO COMPRESSION	H.264
PROTOCOL	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP
DATA RATE	0.1Mbps~6Mbps
VIDEO CONNECTOR	BNC-Female @ 1 Volt P-P & RJ-45
COMMUNICATION PORT	RJ-45 @ 10/100Mbps Base-T Ethernet LAN and 48VDC PoE IEEE 802.3af
POWER SUPPLY	Sold Separately - #PS-122C (12VDC Only) or #PS-4850PoE (PoE 48VDC Only)
POWER CONNECTOR	2.1mm Barrel (12VDC Only) & RJ45 (PoE 48VDC Only)
CAMERA CURRENT CONSUMPTION	700mA @ 12VDC (IR ON)
POE CURRENT CONSUMPTION	8.4 Watts @ 48VDC (IR ON)
CAMERA CONSTRUCTION	Rugged All-Weather IP-66 Rated Cast Aluminum Design
CAMERA DIMENSIONS	14" x 9" x 6" (364mm x 234mm x 147mm)
CAMERA WEIGHT	1.7KG (3.7lbs)
OPERATING TEMPERATURE RANGE	-40°F to +170°F (-40°C to 77°C)
SOFTWARE	Includes License-Free 64 Channel Client Management Software
NOTE	Add a Video Network Bridge to Make this Camera Wireless

CMS INCLUDED

Specifications are Subject to Change Without Notice

KIT INCLUDES

- NETWORK BULLET CAMERA
- MOUNTING BRACKET
- OWNER'S MANUAL
- CLIENT MANAGEMENT SOFTWARE
- 100% PERFORMANCE GUARANTEE
- ONE YEAR LIMITED WARRANTY



1016C Sutton Drive, Unit 6, Burlington, ON Canada L7L 6B8
Tel: 905.336.9665 Fax: 905.336.9662 www.VideoTransmitters.com

VIDEOCOMM
TECHNOLOGIES

© Copyright 2015 1156488 Ontario Inc.

Available from A1 Security Cameras
www.a1securitycameras.com email: sales@a1securitycameras.com