

2MP HIGH-SPEED NETWORK PTZ CAMERA

**PRO
SERIES**



IPC-2MPTZ400 – 2MP PRO-Series All-Weather IR-400' Range 4.7-94mm High-Speed Network PTZ Camera

PRO-Series 2-MegaPixel All-Weather Network PTZ Camera featuring an enhanced **4.7-94mm (20x Optical) zoom lens** with high-intensity **infrared night-vision up to 400 Feet**. Perfect for all-weather 360° surveillance applications including: Parking lots, storage facilities, schools, hospitals and other high-risk areas.



ADVANTAGES

- High-Definition H.264 **2-MegaPixels (1920 x 1080) @ 30fps**
- **Intense IR Night-Vision Range up to 400 Feet**
- **Dynamic 4.7mm-94mm (20 x Optical) Zoom Lens**
- High Speed Pan & Tilt up to 300°/s
- Vandal-Resistant IP-66 Rated All-Weather Design
- ONVIF Compliant for Easy Installation
- Includes License-Free 64 Channel Client Management Software
- Perfect for Parking Lots, Shipping Yards, Storage Facilities, Warehouses & Construction Sites
- 100% Performance Guarantee

APPLICATIONS INCLUDE



SCHOOLS



PARKING LOTS







GAS STATIONS



HOSPITALS

SPECIFICATIONS

CAMERA TYPE	1/2.8" Micron CMOS Sensor + TI DaVinci TMS320DM368 DSP	CMS INCLUDED
RESOLUTION	1080P 2MP @ 30fps (1920x 1080) D1: 2MP @ 30fps (720x 576) CIF: 2MP @ 30fps (352 x 288)	
VIDEO FORMAT	NTSC / PAL	
STANDARDS	ONVIF 2.0	
CAMERA LENS TYPE	4.7-94mm (20x Optical Zoom) with 3.4° - 54.8° Viewing Angle	
CAMERA S/N RATIO	>45dB	
CAMERA SYNC / WHITE BALANCE	Automatic	
CAMERA ELECTRONIC SHUTTER	1/50~1/10,000 Seconds	
CAMERA IR RANGE	IR Array up to 400 Feet	
CAMERA MINIMUM ILLUMINATION	Color 0.3 Lux	
CAMERA IR CUT FILTER	Automatic / Mechanical	
DWDR FUNCTION	Digital Wide Dynamic Range	
TOUR GROUP	4-Groups 24 Preset Positions Each	
PATTERN SCAN	4-Groups 256 Preset Positions Each	
ROTATION RANGE	Pan Range: 360° - Continuous Tilt Range: 0° -90°	
ROTATION SPEED	Manual: 95 °-140 °/s Preset: 300°/s	
VIDEO COMPRESSION	H.264	Optional Corner Mount #BRK-IPC400CMB
PROTOCOL	TCP/IP, RTSP, RTP, RTCP, HTTP, HTTPS, FTP, DHCP, MUDP, SMTP, CIFS, UPNP, PPPoE, NTP, DDNS	
DATA RATE	0.16Mbps~8Mbps	
VIDEO CONNECTOR	BNC-Female @ 1 Volt P-P & RJ-45	
COMMUNICATION PORT	RJ-45 (10/100Mbps Base-T Ethernet LAN)	
POWER SUPPLY INCLUDED	12VDC 5Amp #PS-12500CLX	
POWER CONNECTOR	2.1mm Barrel	
CAMERA CURRENT CONSUMPTION	1100mA @ 12VDC (IR ON)	
POE CURRENT CONSUMPTION	13.2 Watts @ 48VDC (IR ON)	Optional Corner Mount #BRK-IPC400CMB
CAMERA CONSTRUCTION	Rugged All-Weather IP-66 Rated Cast Aluminum Design + Polycarbonate Dome	
CAMERA DIMENSIONS	12" x 16" x 9" (305mm x 406mm x 229mm)	
CAMERA WEIGHT	4.9KG (10.8lbs)	
OPERATING TEMPERATURE RANGE	-40°F to +170°F (-40°C to 77°C)	Optional Corner Mount #BRK-IPC400CMB
SOFTWARE	Includes License-Free 64 Channel Client Management Software	
NOTE	Add a Video Network Bridge to Make this Camera Wireless	

**Optional Wall Mount
#BRK-IPC400WM**

**Optional Pole Mount
#BRK-IPC400PM**

**Optional Corner Mount
#BRK-IPC400CMB**

KIT INCLUDES

- NETWORK PTZ CAMERA
- POWER SUPPLY
- DC POWER JACK CONNECTOR
- OWNER'S MANUAL
- CLIENT MANAGEMENT SOFTWARE (CD-ROM)
- 100% PERFORMANCE GUARANTEE
- ONE YEAR LIMITED WARRANTY



Specifications are Subject to Change Without Notice

1016C Sutton Drive, Unit 6, Burlington, ON Canada L7L 6B8
Tel: 905.336.9665 Fax: 905.336.9662 www.VideoTransmitters.com

VIDEO COMM
TECHNOLOGIES

Available from A1 Security Cameras
www.a1securitycameras.com email: sales@a1securitycameras.com

© Copyright 2015 1156488 Ontario Inc.