

## AXIS P1405-E Network Camera

Compact and cost-effective HDTV surveillance

The bullet-style AXIS P1405-E provides excellent image quality in HDTV 1080p resolution. It features a varifocal P-iris lens. P-iris control provides optimal depth of field, resolution, image contrast and clarity. AXIS P1405-E supports Axis' Corridor Format for vertically oriented video streams of areas such as corridors, hallways or aisles. The pixel counter assures that the pixel resolution of an object fulfills requirements for identification purposes. Remote zoom and focus eliminate the need for hands-on fine tuning. The outdoor-ready camera has an adjustable weather shield protecting it from rain, snow and direct sunlight.

- > **HDTV 1080p resolution at full frame rate**
- > **Day & Night functionality**
- > **Edge storage**
- > **H.264 and Motion JPEG**
- > **Ease of installation**



## AXIS P1405-E Network Camera

Camera		Notification: email, HTTP, HTTPS and TCP and SNMP trap Video recording to edge storage Pre- and post-alarm video buffering PTZ preset, Overlay text
Image sensor	Progressive scan CMOS 1/2.8"	
Lens	2.8–10 mm, F1.6 Horizontal angle of view 34° – 93° Varifocal, Autofocus, Remote focus and zoom, P-Iris control, IR corrected	
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	Color: 0.35 lux at F1.6 B/W: 0.07 lux at F1.6	
Shutter time	1/28000 s to 2 s with power line frequency 50 Hz 1/33500 s to 2 s with power line frequency 60 Hz	
Video		
Video compression	H.264 Main and Baseline profiles (MPEG-4 Part 10/AVC) Motion JPEG	
Resolutions	1920x1080 HDTV 1080p to 160x90 Meets relevant parts of SMPTE 274M (HDTV 1080p)	
Frame rate	Up to 25/30 fps (50/60 Hz) in all resolutions	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG, Controllable frame rate and bandwidth, VBR/MBR H.264	
Image settings	Manual shutter time, Compression, Color, Brightness, Sharpness, White balance, Exposure control, Exposure zones, Backlight compensation, Fine tuning of behavior at low light, Text and image overlay, Privacy masks Wide Dynamic Range-Dynamic Contrast Rotation: 0°, 90°, 180°, 270°, including Corridor Format	
Pan/Tilt/Zoom	Digital PTZ	
Network		
Security	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log	
Supported protocols	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://www.axis.com">www.axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at <a href="http://www.onvif.org">www.onvif.org</a>	
Analytics	Video motion detection Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a>	
Event triggers	Detectors: Day/Night Mode, Live Stream Accessed Tampering Hardware: Network, Temperature Input Signal: Manual Trigger, Virtual Inputs Storage: Disruption, Recording System: System Ready Time: Use Schedule, Recurrences	
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email	
		<b>Built-in installation aids</b> Pixel counter, Remote zoom (3–3.5x optical), Remote focus <b>Data streaming</b> Event data <b>General</b> <b>Casing</b> IP66- and NEMA 4X-rated casing (polyester polycarbonate blend) <b>Memory</b> 256 MB RAM, 128 MB Flash <b>Power</b> Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Max 3.7 W <b>Connectors</b> RJ-45 10BASE-T/100BASE-TX PoE <b>Edge storage</b> Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a> <b>Operating conditions</b> -10 °C to 50 °C (14 °F to 122 °F) Humidity 10–100% RH (condensing) <b>Storage conditions</b> -40 °C to 65 °C (-40 °F to 149 °F) <b>Approvals</b> EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN22 Class B, KN24, IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, IEC/EN 60529 IP66, NEMA 250 type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-27 EN 55022 Class B <b>Weight</b> With weather shield: 776 g (1.71 lb) <b>Dimensions</b> Ø132 x 260 mm (Ø5 3/16 x 10 1/4 in) <b>Included accessories</b> Mounting bracket, Drill template, Installation Guide, Windows decoder 1-user license Weather shield <b>Optional accessories</b> AXIS T94F01M J-Box/Gang Box Plate AXIS T91A47 Pole Mount AXIS T94P01B Corner Bracket AXIS T94F01P Conduit Back Box Axis PoE Midspans For more accessories, see <a href="http://www.axis.com">www.axis.com</a> <b>Video management software</b> AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/techsup/software">www.axis.com/techsup/software</a> <b>Languages</b> English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese <b>Warranty</b> Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a> a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit ( <a href="http://www.openssl.org/">http://www.openssl.org/</a> ), and cryptographic software written by Eric Young ( <a href="mailto:ey@cryptsoft.com">ey@cryptsoft.com</a> ).

More information is available at [www.axis.com](http://www.axis.com)