

AXIS P1428-E Network Camera

Compact and cost-effective 4K Ultra HD surveillance

The bullet-style AXIS P1428-E provides excellent image quality in 8 megapixel resolution. The high resolution enables the camera to cover a large area in exceptional detail for high quality identification. The camera features a varifocal P-iris lens. P-iris control provides optimal depth of field, resolution, image contrast and clarity. The pixel counter assures that the required pixel resolution is met, and remote zoom and focus eliminate the need for hands-on fine tuning. The input/output port can be used for alarm notification or to control a relay. The outdoor-ready camera has an adjustable weather shield protecting it from rain, snow and direct sunlight.

- > 4K Ultra HD resolution at full frame rate
- > Day & Night functionality
- > Edge storage
- > Ease of installation
- > I/O support



AXIS P1428-E Network Camera

Camera			
Image sensor	Progressive scan CMOS 1/2.5"	External output activation Video recording to edge storage Pre- and post-alarm video buffering PTZ preset, Overlay text	
Lens	3.3–9.8 mm, F1.6 Horizontal angle of view 35° – 109° Varifocal, Autofocus, Remote focus and zoom, P-Iris control, IR corrected	Built-in installation aids Pixel counter, Remote zoom (3–3.5x optical), Remote focus	
Day and night	Automatically removable infrared-cut filter	Data streaming Event data	
Minimum illumination	Color: 1.4 lux at F1.6 B/W: 0.3 lux at F1.6	General	
Shutter time	1/32500 s to 1/2 s	Casing	IP66- and NEMA 4X-rated casing (polyester polycarbonate blend)
Video		Memory	1024 MB RAM, 256 MB Flash
Video compression	H.264 High, Main and Baseline profiles (MPEG-4 Part 10/AVC) Motion JPEG	Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Max 12.9 W
Resolutions	3840x2160 4K Ultra HD to 160x90 Meets relevant parts of SMPTE ST 2036-1 (UHDTV)	Connectors	RJ-45 10BASE-T/100BASE-TX/1000BASE-T PoE I/O: 4-pin terminal block for 1 alarm input and 1 output
Frame rate	Up to 25/30 fps (50/60 Hz) in all capture modes (UHD, 5 MP and QHD) as well as all other resolutions	Edge storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG, Controllable frame rate and bandwidth, VBR/MBR H.264	Operating conditions	–30 °C to 50 °C (–22 °F to 122 °F) Humidity 10–100% RH (condensing)
Image settings	Manual shutter time, Compression, Color, Brightness, Sharpness, White balance, Exposure control, Exposure zones, Backlight compensation, Fine tuning of behavior at low light, Text and image overlay, Privacy masks Wide Dynamic Range-Dynamic Contrast Rotation: 0°, 180°	Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F)
Pan/Tilt/Zoom	Digital PTZ	Approvals	EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN22 Class B, KN24, IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, IEC/EN 60529 IP66, NEMA 250 type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-27 EN 55022 Class B
Network		Weight	With weather shield: 854 g (1.88 lb)
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log	Dimensions	Ø132 x 260 mm (Ø5 3/16 x 10 1/4 in)
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Included accessories	Mounting bracket, Drill template, Installation Guide, Windows decoder 1-user license Weather shield
System integration		Optional accessories	AXIS T94F01M J-Box/Gang Box Plate AXIS T91A47 Pole Mount AXIS T94P01B Corner Bracket AXIS T94F01P Conduit Back Box Axis PoE Midspans For more accessories, see www.axis.com
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at www.onvif.org	Video management software	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
Analytics	Video motion detection Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, see www.axis.com/acap	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese
Event triggers	Detectors: Day/Night Mode, Live Stream Accessed Tampering Hardware: Network, Temperature Input Signal: Manual Trigger, Virtual Inputs Storage: Disruption, Recording System: System Ready Time: Use Schedule, Recurrences	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP and SNMP trap	<p>a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/), and cryptographic software written by Eric Young (ey@cryptsoft.com).</p> <p>More information is available at www.axis.com</p>	