

AXIS P3215-V Network Camera

Streamlined and versatile varifocal with HDTV 1080p

AXIS P3215-V is a streamlined fixed dome with HDTV 1080p video quality and up to 2 MP resolution. It features a varifocal lens, P-Iris control and day/night functionality. P-Iris control provides optimal depth of field, resolution, image contrast and clarity. Remote zoom and focus eliminate the need for hands-on fine tuning, and day and night functionality provide superb image quality both in daylight and dark conditions. AXIS P3215-V provides multiple, individually configurable H.264 and Motion JPEG video streams. With a built-in memory card slot, the camera enables local storage of video. The IK08-rated AXIS P3215-V is dust-resistant and impact-resistant.

- > **HDTV 1080p and H.264**
- > **Day/night functionality**
- > **Remote zoom and focus**
- > **P-Iris control**
- > **IK08 impact-resistant**



AXIS P3215-V Network Camera

Camera		Send video clip Overlay text
Image sensor	Progressive scan RGB CMOS 1/2.8"	Data streaming Event data
Lens	Varifocal, 3.0-10.5 mm, F1.4 Horizontal angle of view: 95°-34° Vertical angle of view: 49°-20° Remote focus and zoom, P-Iris control, IR corrected	Built-in installation aids Remote zoom, Remote focus, Pixel counter
Day and night	Automatically removable infrared-cut filter	General
Minimum illumination	Color: 0.25 lux, F1.4 B/W: 0.05 lux, F1.4	Casing Aluminum inner camera module with encapsulated electronics IK08 impact-resistant, dust-resistant, polycarbonate casing with dehumidifying membrane Color: White NCS S 1002-B For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.
Shutter time	1/33500 s to 2 s	Memory 256 MB RAM, 128 MB Flash
Camera angle adjustment	Pan ±180°, Tilt 90°, Rotation ±95°	Power Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 2 Max 4.8 W, Typical 3.5 W
Video		Connectors RJ45 10BASE-T/100BASE-TX PoE
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and Baseline Profile Motion JPEG	Edge storage Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Resolutions	1920x1080 to 160x90	Operating conditions 0 °C to 50 °C (32 °F to 122 °F) Humidity 10 to 85% RH (non-condensing)
Frame rate	Up to 25/30 fps with power line frequency 50/60 Hz in all resolutions	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F)
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth, VBR/MBR H.264	Approvals EN 55022 Class B, EN 61000-6-1, EN 61000-6-2, EN 55024, EN 50121-4, IEC 62236-4, FCC Part 15 Subpart B Class A+B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22 Class B, IEC/EN/UL 60950-1, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP42, IEC/EN 62262 IK08
Multi-view streaming	2 individually cropped out view areas	Weight 550 g (1.2 lb)
Image settings	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control (including automatic gain control), Exposure zones, Backlight compensation, Fine tuning of behavior at different light levels, WDR - Dynamic Contrast, Text and image overlay, Mirroring of images, Privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format	Dimensions 101 x 149 x 149 mm (4.0 x 5.9 x 5.9 in)
Pan/Tilt/Zoom	Digital PTZ	Included accessories Installation Guide, Windows decoder 1-user license, Mounting bracket, Cable gasket, Resistorx T20 L-key, Drill template
Network		Optional accessories AXIS T90B Illuminators AXIS ACI Conduit Bracket B AXIS T94S01S Mounting Bracket AXIS ACI Conduit Adapters AXIS T94K01L Recessed Mount AXIS T94K01D Pendant Kit AXIS Skin Cover C, Black
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	Video management software AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3(MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Languages German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese
System integration		Warranty Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at www.onvif.org	a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com). More information is available at www.axis.com
Analytics	Video motion detection, Active tampering alarm Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, see www.axis.com/acap	
Event triggers	Analytics, Edge storage events	
Event actions	File upload: FTP, SFTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS, TCP and SNMP trap Video recording to edge storage Pre- and post-alarm video buffering	