

AXIS P3214-VE Network Camera

Streamlined and versatile varifocal with HDTV 720p

AXIS P3214-VE is a streamlined, outdoor-ready fixed dome with HDTV 720p video quality and up to 1.3 MP resolution. It features a varifocal lens, P-Iris control and day/night functionality. P-Iris control provides optimal depth of field, resolution, image contrast and clarity. Remote zoom and focus eliminate the need for hands-on fine tuning, and day and night functionality provide superb image quality both in daylight and dark conditions. AXIS P3214-VE provides multiple, individually configurable H.264 and Motion JPEG video streams. With a built-in memory card slot, the camera enables local storage of video. The IK10-rated AXIS P3214-VE is dust-resistant and vandal-resistant.

- > **HDTV 720p and H.264**
- > **Day/night functionality**
- > **Remote zoom and focus**
- > **P-Iris control**
- > **IK10 vandal-resistant**



AXIS P3214-VE Network Camera

Camera		Data streaming	Event data
Image sensor	Progressive scan RGB CMOS 1/2.8"	Built-in installation aids	Remote zoom, Remote focus, Pixel counter
Lens	Varifocal, 2.8-10 mm, F1.6 Horizontal angle of view: 92°-33° Vertical angle of view: 49°-20° Remote focus and zoom, P-Iris control, IR corrected	General	
Day and night	Automatically removable infrared-cut filter	Casing	Aluminum inner camera module with encapsulated electronics IP66- and NEMA 4X-rated, IK10 impact-resistant, polycarbonate casing with dehumidifying membrane PVC free Color: White NCS S 1002-B For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.
Minimum illumination	Color: 0.3 lux, F1.6 B/W: 0.06 lux, F1.6	Memory	256 MB RAM, 128 MB Flash
Shutter time	1/33500 s to 2 s	Power	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Max 8.4 W, Typical 3.5 W
Camera angle adjustment	Pan ±180°, Tilt 90°, Rotation ±95°	Connectors	RJ45 10BASE-T/100BASE-TX PoE
Video		Storage	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and Baseline Profile Motion JPEG	Operating conditions	-30 °C to 50 °C (-22 °F to 122 °F) Humidity 10 to 100% RH (condensing)
Resolutions	1280x960 to 160x90	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Frame rate	Up to 25/30 fps with power line frequency 50/60 Hz in all resolutions	Approvals	EN 55022 Class B, EN 61000-6-1, EN 61000-6-2, EN 55024, EN 50121-4, IEC 62236-4, FCC Part 15 Subpart B Class A+B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22, KCC KN22 Class B, KN24, IEC/EN/UL 60950-22, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6 Class 4M4, IEC 60068-2-27 Class 4M4, IEC 60068-2-14, IEC 60068-2-78 Class 4K3, IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC/EN 62262 IK10
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth, VBR/MBR H.264	Weight	790 g (1.7 lb)
Multi-view streaming	2 individually cropped out view areas	Dimensions	101 x 149 x 149 mm (4.0 x 5.9 x 5.9 in)
Image settings	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control (including automatic gain control), Exposure zones, Backlight compensation, Fine tuning of behavior at low light, WDR - Dynamic Contrast, Text and image overlay, Mirroring of images, Privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format	Included accessories	Installation Guide, Windows decoder 1-user license, Mounting bracket, Cable gasket, Resistorex T20 L-key, Drill template Weather shield
Pan/Tilt/Zoom	Digital PTZ	Optional accessories	AXIS T90B Illuminators AXIS ACI Conduit Bracket A AXIS T94T01D Pendant Kit including weather shield AXIS T94M01L Recessed Mount AXIS T94T01S Mounting Bracket AXIS T91 Mounts AXIS T98A17-VE Surveillance Cabinet
Network		Video management software	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log, Centralized Certificate Management	Languages	German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3(MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
System integration		a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).	
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at www.onvif.org	Environmental responsibility: www.axis.com/environmental-responsibility	
Analytics	Video motion detection, Active tampering alarm Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, see www.axis.com/acap		
Event triggers	Analytics, Edge storage events		
Event actions	File upload: FTP, SFTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS, TCP and SNMP trap Video recording to edge storage Pre- and post-alarm video buffering Send video clip Overlay text		