

Video | AUTODOME 5000 PTZ Camera (720TVL Sensor)

AUTODOME 5000 PTZ Camera (720TVL Sensor)

www.boschsecurity.com**BOSCH**
Invented for life


- ▶ True day/night PTZ dome camera with 432x zoom (36x extended zoom, 12x digital zoom)
- ▶ Ultra high resolution up to 720TVL (960H with WDR)
- ▶ Vandal-resistant housing rated to IK10
- ▶ Privacy masking, image enhancement, motion detection and Wide Dynamic Range
- ▶ Indoor and outdoor models available for a wide range of applications

The AUTODOME 5000 Series day/night PTZ camera is based on a high-resolution 960H sensor that is capable of delivering a maximum resolution of 720TVL. The Wide Dynamic Range of the sensor allows the camera to capture detailed images even in challenging high-contrast scenes.

The camera provides variable pan/tilt speeds ranging from a fast patrol of 360° per second to a slow ramble of 5° per second with 0.225° pan/tilt accuracy. The 360° endless rotation and 0° to 180° tilt travel help to track an object passing directly beneath the camera. The AUTODOME 5000 features an RS-485 port, compatible with the Bosch LTC 5136 controller and the MIC-BP3 Biphasic Converter for quick setup and control. The camera also supports the OSRD and the Pelco P/D protocols for easy integration with existing surveillance systems.

Certifications and approvals

Electromagnetic Compatibility (EMC)	Complies with FCC part 15, ICES-003, EN 55022:1998, EN 50130-4:1995, EN61000-3-2:2000 and EN 61000-3-3:1995
Safety	EN60950-1:2006, +A11:2009, A1:2010, +A12:2011 / UL 60950-1
Ingress Protection Rating	IP66
IK Code	IK10

Installation/configuration notes

AUTODOME 5000 Dimensions

1	Diameter without sunshield (indoor models)
2	Diameter with sunshield (outdoor models)

Parts included
Technical specifications
Camera

System	PAL or NTSC
Image Sensor	960H, 1/4-in. Double Scan CCD, 720TVL sensor resolution
Effective Pixels (HxV)	Approx. 570,000; 976 x 582 (PAL) Approx. 480,000; 976 x 494 (NTSC)
Horizontal Resolution	720TVL (960H with WDR capability)
Lens	3.43 mm – 120 mm, F1.6~F4.5
Focus	Constant, Manual, Spot
Iris	Auto, Manual
Optical Zoom Field of View (DxHxV)	Wide: 72.3° x 57.8° x 43.4° Tele: 2.13° x 1.70° x 1.28°
Gain Control	Auto, Manual
Digital Zoom	12x

Sensitivity (typical)	30 IRE
• Day mode	0.1 lux, under F1.6
• Night mode (black and white)	0.01 lux, under F1.6
Electronic Shutter Speed	
• PAL	1/50 to 1/10000 second
• NTSC	1/60 to 1/10000 second
Wide Dynamic Range (WDR)	60 dB
Signal-to-Noise Ratio	>50 dB (with AGC off)
White Balance	Auto, Manual, Indoor, Outdoor, ATW
Video output	1.0 Vp-p / 75Ω, BNC

Mechanical

Pan Range	360° continuous
Tilt Range	0° to 180°
Manual Speed	0.5° to 90° /second
Pre-position Speed	5° to 360° /second
Preset Accuracy	0.225°
Flip	Image: 180° Mechanical : 90°

Electrical

Input Voltage	24 VAC, 50/60 Hz
Power Consumption, typical	
• Indoor Models	20 W (without heater)
• Outdoor Models	50 W (with heater)

Miscellaneous

Privacy Masking	20 individually-configurable masks
DNR	2 DNR / 3 DNR
AGC Control	Auto, Manual
Backlight Compensation	On, Off
Proportional Pan / Tilt	On, Off
Image Enhancement	Zoom, Stabilize, Off
Night Mode	On, Off, Auto
Auto SensUp Max	2x to 60x or Off
Prepositions	99
Tours	8
AutoPan	4

Preset Tours	8
Camera Setup / Control	RS-485
Communications Protocols	Bosch OSD, Pelco D/P
Supported Languages	English, Dutch, French, German, Italian, Polish, Portuguese, Russian, Spanish, Simplified Chinese

Alarm Connections

Inputs	Four (4): 5V 10 kΩ Pull Up
Outputs	Two (2): Relay output, max. 2 A, 30 VDC / 0.5 A, 125 VAC

Environmental

Ingress Protection Rating	IP66
Operating Temperature	
• Indoor Models	0°C to 50°C (32°F to 122°F)
• Outdoor Models	-40°C to +50°C (-40°F to 122°F)
Storage Temperature	-20°C to +70°C (-4°F to 158°F)
Humidity	10% to 90% relative, non-condensing
Heater	Turns on at -7°C (19.4°F), Turns off at +3°C (37.4°F)

Construction

Dimensions (D x H)	
• With Sunshield	Φ 208 mm x 295.5 mm (8.19 in. x 11.63 in.)
• Without Sunshield	Φ 187 mm x 295.5 mm (7.36 in. x 11.63 in.)
Weight	3.3 kg (8 lb) with sunshield
Construction Material	
• Housing	Die-cast aluminum
• Sunshield	Outdoor Grade Plastic
Standard Color	White (RAL 9003)

Ordering information

AUTODOME 5000, 960H, 36x PTZ Camera PAL, Outdoor
Outdoor PAL PTZ camera with a clear rugged bubble
Order number **VEZ-513-EWCR**

AUTODOME 5000, 960H, 36x PTZ Camera NTSC, Outdoor
Outdoor NTSC PTZ camera with a clear rugged bubble
Order number **VEZ-523-EWCR**

AUTODOME 5000, 960H, 36x PTZ Camera PAL, Indoor
Indoor PAL PTZ camera with a clear rugged bubble
Order number **VEZ-513-IWCR**

AUTODOME 5000, 960H, 36x PTZ Camera NTSC, Indoor
Indoor NTSC PTZ camera with a clear rugged bubble
Order number **VEZ-523-IWCR**

AUTODOME 5000, 960H, 36x PTZ Camera PAL, Outdoor, Tinted Bubble
Outdoor PAL PTZ camera with a tinted rugged bubble
Order number **VEZ-513-EWTR**

AUTODOME 5000, 960H, 36x PTZ Camera NTSC, Outdoor, Tinted Bubble
Outdoor NTSC PTZ camera with a tinted rugged bubble
Order number **VEZ-523-EWTR**

AUTODOME 5000, 960H, 36x PTZ Camera PAL, Indoor, Tinted Bubble
Indoor PAL PTZ camera with a tinted rugged bubble
Order number **VEZ-513-IWTR**

AUTODOME 5000, 960H, 36x PTZ Camera NTSC, Indoor, Tinted Bubble
Indoor NTSC PTZ camera with a tinted rugged bubble
Order number **VEZ-523-IWTR**

Accessories

UPA-2450-60 Power Supply, 120 V, 60 Hz
Indoor power supply for camera. 120 VAC, 60 Hz In; 24 VAC, 50 VA Out
Order number **UPA-2450-60**

UPA-2450-50 Power Supply, 220 V, 50 Hz
Indoor power supply for camera. 220 VAC, 50 Hz In; 24 VAC, 50 VA Out
Order number **UPA-2450-50**

MIC-BP3 Biphase Converter
Biphase converter for IR power supplies or non-IR power supplies without a free expansion slot available
Order number **MIC-BP3**

LTC 5136/51 AUTODOME Controller
with 16 outputs for AUTODOME cameras or for Allegiant Receiver/Drivers units, 230 VAC, 50/60 Hz
Order number **LTC 5136/51**

LTC 5136/61 AUTODOME Controller
with 16 outputs for AUTODOME cameras or for Allegiant Receiver/Drivers units, 110 VAC, 50/60 Hz
Order number **LTC 5136/61**

VEZ-A5-WMB Wall Mount Bracket
Mount for installing an AUTODOME 5000 camera on a wall
Order number **VEZ-A5-WMB**

VEZ-A5-PP AUTODOME 5000 Pipe Mount
Mount for installing an AUTODOME 5000 camera onto a pipe.
Order number **VEZ-A5-PP**

AUTODOME 5000 Recessed MountOrder number **VEZ-A5-IC****NDA-ADPTR-NPTMET NPT-Metric Adapter**

NPT-to-Metric Adapter (female-to-M33 male adapter)
for use with NPT1.5 pipes with pipe mount (VEZ-A5-PP) and roof mount (VGA-ROOF-MOUNT).

Order number **NDA-ADPTR-NPTMET****VDA-POMT-PTZDOME Pole Mount Adapter**

Pole mount adapter for use with the appropriate wall
mount for indoor and outdoor applications.

Order number **VDA-POMT-PTZDOME****VDA-CMT-PTZDOME Corner Mount Adapter**

Corner mount adapter for use with the appropriate
wall mount for indoor or outdoor pole (mast)
applications

Order number **VDA-CMT-PTZDOME****Represented by:****Americas:**

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
203 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com