


4 Port + 1 Uplink PoE Switch
 100Mbps | 65W | 802.3af



4 PoE PORTS

Plus one uplink

100Mbps

Data transfer rate

65W MAX POWER

15.4W per port

IEEE 802.3af

Standard

4 DIP SWITCHES

Full power on/off control

POWER PROTECTION

On low powered devices

UNMANAGED

Ports automatically detect devices

Standard

IEEE 802.3af
 IEEE 802.3 10BASE-T
 IEEE 802.3u 100BASE-TX
 IEEE 802.3x Flow Control

Number of PoE Ports

4 PoE + 1 Uplink

MAC Address Table

2K

Buffer Memory

512KB

Transmission Method

Store and Forward

Filtering/Forwarding Rates

100Mbps Port - 148,800pps
 10Mbps Port - 14,880pps

Transmission Media

100BaseTx Cat5 UTP/STP
 10BaseT Cat3, 4, 5 UTP/STP

LED Indicators

Per Port: Link/Act w/ 10/100Mbps, On/Off
 Per Unit: Power

Power Input

90-260VAC, 50-60Hz

Power Output

48VDC 1.25A

Power Consumption

65W Max, 15.4W per Port

Dimensions

4.7" x 3.5" x 1.1"

Weight

1.3 lbs

Operating Temperature

32°F to 131 °F

Storage Temperature

-4°F to 194°F

Humidity

10 to 90% RH (Non-condensing)

Certifications

FCC Class B, CE