

Passive Video Balun Transceiver

LTAB3020T

Designed for all HD-TVI models, 2MP and 1.3MP High Definition Transmission Signal up to 650ft



Key Features:

Passive Video Balun Transceiver

Designed for all HD-TVI models, 2MP and 1.3MP High Definition Transmission Signal up to 650ft

Save Installation Time and Quickly Connect to Cameras from DVRs Easily

Specifications:

Transmission signal	1 channel
Transmission distance	720P TVI: 650ft (max) / 1080P TVI: 650ft (max);
Category Type	UTP CAT5/5E/6
Coaxial video connector	BNC-M
Twisted-pair video connector	Push-Terminal
Compatible Format	HDTV
Resolution	720/1080P
Anti-interference	>60db
ESD	1a contact discharge electricity level3 1b air discharge electricity level3 Per:IEC61000-4-2
Coaxial cable connector	2KV (common-code) Per: IEC1000-4-5
UTP cable connector	2KV (different-code), 4KV (common-code), Per: IEC1000-4-5
Dimension (L*W*H)	2" x 0.8" x0.7"(53mm x 20mm x 17mm)
Shell	ABS
Color	Black
N. W.	25g
MTBF	>10000H
Operating Temperature	-10-55°C
Storage Temperature	-20-70°C
Humidity	0-95% (non-condensing)