


## AL600ULB Power Supply/Charger

### Description

Altronix AL600ULB UL Recognized power supply/charger converts 28VAC/200VA input into a single 12VDC or 24VDC non power-limited output. It also offers a suite of features that includes AC fail supervision, battery presence, and low battery supervision.



AL600ULB

### Specifications

#### Input

Voltage Two (2) 28VAC/100VA, 1A transformers.

#### Output

Voltage 12VDC or 24VDC selectable.  
Current 6A continuous supply current.  
Other Short circuit and thermal overload protection.  
Filtered and regulated.

#### Back-up Battery *(not included)*

Type Sealed lead acid or gel type.  
Failover Upon AC loss, instantaneous.

#### Supervision

AC Failure Form "C" contacts.  
Battery Form "C" contacts.

#### Indicators (LED)

Input Input voltage is present.  
DC Output Powered.

#### Agency Listings

Access ControlUL294  
Fire Alarm UL1481

#### Physical and Environmental

Dimensions (L x W x H)  
7.1" x 4.3" x 2.3" (180.3 mm x 109.2 mm x 58.4 mm).  
Product Weight 1.17 lbs. (0.53 kg).  
Shipping Weight 1.25 lbs. (0.57 kg).  
Temperature  
Operating 0°C to 49°C (32°F to 120°F).  
Storage -20°C to 70°C (-4°F to 158°F).  
Relative Humidity 85% +/-5%.  
BTU/Hr (approx.):  
12VDC: 37 BTU/Hr.  
24VDC: 74 BTU/Hr.

## AL600ULB Power Supply/Charger

### Board Dimensions (L x W x H) and Drawing

7.1" x 4.3" x 2.3" (180.3 mm x 109.2 mm x 58.4 mm)

