

ALTV615DC8UL DC CCTV Power Supply

Description

Altronix ALTV615DC8UL is designed with eight (8) individual Class 2 Rated fuse protected power-limited outputs for powering CCTV cameras and other video accessories. It provides 6VDC-15VDC with a total of up to 4A continuous supply current.



Key Features

- Eight (8) fuse protected power-limited outputs.
- 6-15VDC field adjustable output voltage.
- Filtered and electronically regulated outputs.
- Short circuit and thermal overload protection.
- AC Input and DC Output LED indicators.
- Power ON/OFF switch.
- Spare fuses provided.
- UL Listed in the U.S. and Canada.
- CE Approved.
- Model with factory installed 3-wire line cord is available (ALTV615DC8UL3).
- Lifetime Warranty / Made in the U.S.A.

Specifications

Input

Voltage 115VAC, 50/60Hz, 0.9A.

Outputs

Voltage 6-15VDC.
Current Up to 4A.
Outputs Rating 3.5A/250VAC.

Indicators (LED)

Input LED.
Output LED.

Agency Listings

Commercial CCTV Equipment UL2044
Audio, Video and Similar Equipment CSA Standard C22.2
No.1-98
CE European Conformity

Physical and Environmental

Dimensions (H x W x D):
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm).

Weight:

Product Weight 11.5 lbs. (5.22 kg).
Shipping Weight 12.0 lbs. (5.44 kg).

Temperature:

Operating 0°C to 49°C (32°F to 120°F).
Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr.: 12-31 BTU/Hr., depending on output.