

## NetWay16V

### 16-Port PoE/PoE+ Midspan Injector

#### Description


Altronix NetWay16V Midspan injector provides power and passes data for PoE and PoE+ compliant cameras/edge devices. Cameras/edge devices may be located up to 100m from the NetWay unit. A NetWayXT (PoE) or NetWayXTX (PoE+) repeater module can be utilized to extend the distance an additional 100m for a total range of up to 200m. A maximum range of 600m is possible using multiple repeaters, based on camera/device port requirement. NetWay Midspans are capable of supporting non-PoE compliant fixed and PTZ IP cameras utilizing NetWay1512 or NetWay3012 adapters.



#### Key Features

- IEEE 802.3af (15W) and IEEE 802.3at (30W) compliant.
- Sixteen (16) ports for cameras/edge devices over ethernet.
- Speed: 10/100 Mbps.
- 30W maximum power per port.
- Port status LEDs.
- Auto detection and protection of legacy non-PoE cameras/devices.
- Safe and cost-effective power distribution over CAT5/5E/6 LAN infrastructure.
- CE Approved.
- Lifetime Warranty / Made in the U.S.A.

#### Typical Application



## NetWay16V

### 16-Port PoE/PoE+ Midspan Injector

#### Specifications

##### Input

220VAC 50/60Hz, 2.5A.

##### Power

Unit provides PoE / PoE+

30W full power per port.

Total power: 300W.

##### Ethernet

Connectivity: RJ45, auto-crossover.

Wire type: 4-pair CAT5e or better structured cable.

Distance: up to 100m.

Speed: 10/100 BaseT, half/full duplex, auto negotiation.

##### Indicators (LED)

Yellow and Green LED (by RJ45 jack):

IP Link status, 10/100 Base-T/active.

Green LED

Port status.

##### Agency Listings

CE European Conformity.

##### Physical and Environmental

###### Dimensions (W x L x H)

1U rack mount chassis for use in standard EIA 19" rack.

1.625" x 19.125" x 8.5" (41.275mm x 486mm x 216mm).

###### Weight (approx.)

Product Weight: 8.9 lbs. (4.1 kg).

Shipping Weight: 10.2 lbs. (4.63 kg).

###### Temperature

Operating: -20°C to 40°C (-4°F to 104°F).

Storage: -20° to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

###### Operating Altitude:

-304.8 to 3,048m (-1,000 to 10,000 ft.).

BTU/Hr. (approx.): 154 BTU/Hr.

#### Accessories:

##### Repeaters:



NetWayXT

##### NetWayXT

PoE repeater module.

Extends data (video) for 100m.



NetWayXTX

##### NetWayXTX

PoE+ repeater module.

Extends data (video) for 100m.

##### Adapters:



NetWay1512

##### NetWay1512

15W adapter

for conventional IP cameras.



NetWay3012

##### NetWay3012

25W adapter

for conventional IP cameras.