

## ReServ3WP Video Surveillance UPS

### Description

Altronix ReServ3WP Outdoor Video Surveillance UPS is designed to provide power for 12VDC cameras during normal or power outage conditions. Regulated DC outputs.



ReServ3WP

### Specifications

#### Input

Voltage 115VAC, 60Hz, 3.5A.

#### Outputs

16 individual PTC protected power-limited auto-resettable outputs rated 1A each.

Voltage 12VDC.

Current 8A (0.66A per device, 1A max.)  
(Ambient Temperature -33°C to 42°C).

Other Short circuit and thermal overload protection.

#### Back-up Battery (not included)

Type Sealed lead acid or gel type.

Failover Upon AC loss, instantaneous.

#### Supervision

AC Failure Form "C" contacts.

Low Battery Form "C" contacts.

#### Indicators (Audio and LED)

Input Input voltage is present.

DC Output Powered.

Outputs Individual Indicators.

Audio AC Fail and Battery Fail.

#### Agency Listings

UL/cUL UL60950-1 (Information Technology).

CE European Conformity.

#### Physical and Environmental

##### Dimensions (H x W x D)

17.53" x 15.3" x 6.67" (445.3mm x 388.6mm x 169.4mm).

Enclosure accommodates up to two (2) 12VDC/12AH batteries.

NEMA4 / IP66 Rated Enclosure.

Product Weight 14 lbs. (6.35 kg).

Shipping Weight 15.5 lbs. (7.1 kg).

##### Temperature

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.): 49 BTU/Hr.

### Accessories

PMK2 Pole Mount Kit (order separately)

PMK2 pole mount kit is designed to simplify installation of outdoor units.

It accommodates 2" - 8" (diameter) poles.

Kit includes:

- Two (2) powder coated steel mount brackets.
- Four (4) stainless steel bolts.
- Four (4) stainless steel lock washers.
- Two (2) wormgear quick release straps.



PMK2