

## SMP10C24X220 Series Power Supply/Chargers

### Description

Altronix SMP10C24X220 series power supply/chargers convert a 220VAC (working range 198VAC - 256VAC), 50/60Hz input into a single, four (4), eight (8) or sixteen (16) fuse/PTC protected outputs. Outputs are 24VDC with a total of 10A max.



SMP10PM24P4CB220

### Key Features

- Available with 1, 4, 8 or 16 outputs.
- Fused or PTC protected outputs.
- Supervision (where applicable, see Chart below):
  - AC Fail
  - Battery Fail and Low Battery.
- Built-in charger for sealed lead acid or gel type batteries.
- Instantaneous transfer to stand-by batteries.
- Short circuit and overload protection.
- Power On/Off switch.
- Lifetime Warranty / Made in the U.S.A.

### SMP10C24X220 Series Power Supply Configuration Reference Chart

Altronix Model Number	Accessory Power Distribution Module(s)	Number of Outputs	Fused Outputs	PTC Outputs (auto-resettable)	Individual Output Rating (A)	Supervised	220VAC, 50/60Hz Input Current (A)	24VDC Total Output Current (A)	Accommodates Batteries
SMP10C24X220	—	1	—	—	10A	—	1.8A	10A	Two (2) 7AH
SMP10PMC24X220					10A				
SMP10PM24P4220	PD4	4	✓	—	3.5A	✓			
SMP10PM24P4CB220	PD4CB		—	✓	2.5A				
SMP10PM24P8220	PD8	8	✓	—	3.5A				
SMP10PM24P8CB220	PD8CB		—	✓	2.5A				
SMP10PM24P16220	PD16W	16	✓	—	3.5A				
SMP10PM24P16CB220	PD16WCB		—	✓	2.5A				



## SMP1024CX220 Series Power Supply/Chargers

### Specifications

#### Input

Voltage 220VAC (working range 198VAC - 256VAC),  
50/60Hz.

#### Outputs

Voltage 24VDC.  
Current 10A @ 24VDC continuous max.  
Protection Fused 3.5A / PTC 2.5A.  
Other Overvoltage protection  
Filtered and regulated.

#### Back-up Battery *(not included)*

Capacity 7AH / 12VDC (2 within enclosure).  
40 AH / 65 AH (requires separate enclosure).  
Type Sealed lead acid or gel type.  
Failover Upon AC loss, instantaneous.

#### Supervision *(where applicable)*

AC Failure Form "C" contacts.  
Battery Low/Fail Form "C" contacts.

#### Indicators (LED)

Input 220VAC is present.  
DC Output Powered.

#### Physical and Environmental

Dimensions (H x W x D)  
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm).

#### Product Weight / Shipping (approx.)

Model	Product Weight	Shipping Weight
SMP10(PM)C24X220	8.3 lbs. (3.76 kg)	9.3 lbs. (4.22 kg)
SMP10PM24P4(CB)220	8.5 lbs. (3.85 kg)	9.5 lbs (4.31 kg)
SMP10PM24P8(CB)220	8.6 lbs. (3.90 kg)	9.6 lbs (4.35 kg)
SMP10PM24P16(CB)220	8.8 lbs. (3.99 kg)	9.8 lbs. (4.44 kg)

#### Temperature

Operating 0°C to 49°C (32°F to 120°F).  
Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.): 122 BTU/Hr.