A1 SECURITY CAMERAS
The First Name in Security

VERTILINE

Altronix®

Rev. VertiLine8C-05222017

VertiLine8C
CCTV Rack Mount Power Supply

VertiLine8C

Description

Altronix Vertiline8C CCTV Rack Mount Power Supply provides eight (8) fuse protected power outputs in a space saving 1U EIA 19" rack mount chassis which may be rack, wall or shelf mounted. This unit features individually selectable 24VAC and/or 28VAC power outputs with surge suppression.

Specifications

Input

Voltage	115VAC, 60Hz, 1.5A.

Output

Eight (8) individually selectable power outputs with OFF position.

Voltage	24VAC or 28VAC.
Current	5A max. total supply current.
Fusing	Individual outputs' fuses rated @ 3A. Main fuse rated @ 10A.
Other	Short circuit and thermal overload protection. Filtered and regulated.

Indicators (LED)

Master	Illuminated master power disconnect circuit breaker with manual reset.
Output	Eight (8) individual LEDs.

Agency Listings

UL	UL2044 (Commercial CCTV Equipment).
cUL	CSA Standard C22.2 No.1-04, Audio, Video and Similar Equipment.

CE European Conformity.

Physical and Environmental

Dimensions (H x W x D)
1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm).

Product Weight	6.55 lbs. (2.97 kg).
Shipping Weight	7.85 lbs. (3.56 kg).

Temperature

Operating	0ºC to 49ºC (32ºF to 120ºF).
Storage	-20ºC to 70ºC (-4ºF to 158ºF).
Relative Humidity	85% +/-5%.

BTU/Hr. (approx.):
24VAC: 61 BTU/Hr.
28VAC: 72 BTU/Hr.

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA
phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com

Available from A1 Security Cameras
www.a1securitycameras.com email: sales@a1securitycameras.com