

# VertiLine8D

## CCTV Rack Mount Power Supply

### Description

Altronix VertiLine8D CCTV Rack Mount Power Supply provides eight (8) Class 2 rated PTC protected power-limited auto-resettable outputs in a space saving 1U EIA 19" rack mount chassis which may be rack, wall or shelf mounted. This unit features individually selectable 24VAC and/or 28VAC power outputs with surge suppression.



VertiLine8D

### Specifications

#### Input

Voltage 115VAC, 60Hz, 1.5A or  
230VAC, 50/60Hz, 0.8A.

#### Output

Eight (8) individually selectable power outputs with OFF position.

Voltage 24VAC or 28VAC.

Current 5A max. total supply current.

Fusing Individual outputs' PTCs rated @ 2.5A.  
Main fuse rated @ 10A.

Other Short circuit and thermal overload protection.  
Filtered and regulated.

#### Indicators (LED)

Master Illuminated master power disconnect  
circuit breaker with manual reset.

Output Eight (8) individual LEDs.

#### Agency Listings

UL UL2044 (Commercial CCTV Equipment).  
CE European Conformity.  
C-Tick compliant.

#### Physical and Environmental

##### Dimensions (H x W x D)

1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm).

Product Weight 6.55 lbs. (2.97 kg).

Shipping Weight 7.85 lbs. (3.56 kg).

##### Temperature

Operating 0°C to 49°C (32°F to 120°F).

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

##### BTU/Hr. (approx.):

24VAC: 61 BTU/Hr.

28VAC: 72 BTU/Hr.