

## VertiLine8Di CCTV Isolated Rack Mount Power Supply



VertiLine8Di

### Description

Altronix Vertiline8Di CCTV Isolated Rack Mount Power Supply provides eight (8) Class 2 rated PTC protected power-limited auto-resettable outputs in a space saving 1U EIA 19" rack mount chassis which may be rack, wall or shelf mounted. This unit features individually selectable 24VAC and/or 28VAC power outputs with surge suppression.

### Specifications

#### Input

Voltage 115VAC, 60Hz, 2.5A or  
230VAC, 50/60Hz, 1.5A.

#### Output

Eight (8) electronically isoated individually selectable power outputs with OFF position.

Voltage 24VAC or 28VAC.  
Current 8A max. total supply currect.  
Fusing Individual outputs' PTCs rated @ 2.5A.  
Other Short circuit and thermal overload protection.  
Filtered and regulated.

#### Indicators (LED)

Master Illuminated master power disconnect circuit breaker with manual reset.  
Output Eight (8) individual LEDs.

#### Agency Listings

UL UL2044 (Commercial CCTV Equipment).  
cUL CSA Standard C22.2 No.1-04,  
Audio, Video and Similar Equipment.  
CE European Conformity.  
C-Tick compliant.

#### Physical and Environmental

Dimensions (H x W x D)  
1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm).  
Product Weight 9.3 lbs. (4.22 kg).  
Shipping Weight 10.6 lbs. (4.81 kg).  
Temperature  
Operating 0°C to 49°C (32°F to 120°F).  
Storage -20°C to 70°C (-4°F to 158°F).  
Relative Humidity 85% +/-5%.  
BTU/Hr. (approx.):  
24VAC: 96 BTU/Hr.  
28VAC: 115 BTU/Hr.