



eFlowNAV Series Power Supply/Chargers with Multi-Output Access Power Controllers

Description

Altronix eFlowNAV series distribute and switch power to access control systems and accessories. They convert a 220VAC (working range 198VAC - 256VAC), 50/60Hz input into eight (8) independently controlled 12VDC or 24VDC fuse protected outputs. These power outputs can be converted to dry form "C" contacts. Outputs are activated by an open collector sink or normally open (NO) dry trigger input from an Access Control System, Card Reader, Keypad, Push Button, PIR, etc. Units will route power to a variety of access control hardware devices including: Mag Locks, Electric Strikes, Magnetic Door Holders, etc. Outputs will operate in both Fail-Safe and/or Fail-Secure modes. The FACP Interface enables Emergency Egress, Alarm Monitoring, or may be used to trigger other auxiliary devices. The fire alarm disconnect feature is individually selectable for any or all of the eight (8) outputs.



eFlow102NA8V

Key Features

- Eight (8) independently controlled outputs.
- Output options:
 - a) Eight (8) Fail-Safe and/or Fail-Secure power outputs.
 - b) Eight (8) form "C" 5A rated relay outputs.
 - c) Any combination of the above.
- Eight (8) auxiliary power outputs (unswitched).
- Output fuses are rated @ 3.5A.
- Filtered and electronically regulated outputs.
- Supervision:
 - AC Fail
 - Battery Fail and Battery Presence
 - Low power shutdown
- Fire Alarm disconnect (latching or non-latching) is individually selectable for any or all of the eight (8) outputs.
- Alarm output relay indicates that FACP input is triggered.
- Fire Alarm disconnect input options:
 - a) Normally open (NO) or normally closed (NC) dry contact input
 - b) Polarity reversal input from FACP signaling circuit.
- Built-in charger for sealed lead acid or gel type batteries.
- Instantaneous transfer to stand-by batteries.
- CE Approved.
- Lifetime Warranty / Made in the U.S.A.

eFlowNAV Series Power Supply Configuration Reference Chart

Altronix Model Number	Maximum Supply Current for Main and Aux. Outputs (A)		Fuse Protected Outputs	220VAC 50/60 Hz Input Current (A)	Current per ACM8 output (A)	Power Supply Board Input Fuse Rating	Power Supply Board Battery Fuse Rating	ACM8 Board Input Fuse Rating	ACM8 Board Output Fuse Rating
	12VDC	24VDC							
eFlow4NA8V	3.3A	3.6A	8	2.1A	2.5A	5A/250V	7.5A/32V	10A/250V	2.5A/250V
eFlow6NA8V	5.3A	5.6A	8	2.1A	2.5A	5A/250V	10A/32V	10A/250V	2.5A/250V
eFlow102NA8V	9.3A	—	8	2.1A	2.5A	5A/250V	15A/32V	10A/250V	2.5A/250V
eFlow104NA8V	—	9.6A	8	2.7A	2.5A	6.3A/250V	15A/32V	10A/250V	2.5A/250V



eFlowNAV Series Power Supply/Chargers with Multi-Output Access Power Controllers



Specifications

Input

Voltage	220VAC (working range 198VAC - 256VAC), 50/60Hz.
Fusing	Varies, see Reference Chart.

Outputs

Voltage	12VDC or 24VDC, see Reference Chart.
Current	Varies, depending on the model.
Protection	Fused 3.5A.
Auxiliary	2.5A (unswitched).
Other	Overvoltage protection. Filtered and regulated outputs.

Back-up Battery *(not included)*

Capacity	12AH / 12VDC (1 or 2 within enclosure). 18AH / 40AH / 65AH (requires separate enclosure).
Type	Sealed lead acid or gel type.
Fuse Rating	Varies, see Reference Chart.
Failover	Upon AC loss, instantaneous.

Fire Alarm Disconnect

Supervised	Latching or non-latching, individually selectable for any or all of the eight (8) outputs.
EOL	10K Resistor.

Supervision

AC Failure	Form "C" contacts.
Battery	Form "C" contacts.

Low DC Power Shutdown

Shuts down DC output terminals if battery voltage drops below 71-73% for 12V units and 70-75% for 24V units (depending on the power supply). Prevents deep battery discharge.

Indicators (LED)

Input	220VAC is present.
DC Output	Powered.
Battery	Discharged or not connected.
Relays	Individual LEDs indicate outputs are triggered (relays energized).
FACP	Indicates FACP disconnect is triggered.

Agency Listings

CE	European Conformity
----	---------------------

Physical and Environmental

Dimensions (H x W x D)

15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm).
Accommodates up to two (2) 12VDC/12AH batteries.

Product Weight / Shipping (approx.)

Model	Product Weight	Shipping Weight
eFlow4NA8V	8.65 lbs. (3.92 kg)	9.95 lbs. (4.51 kg)
eFlow6NA8V	8.6 lbs. (3.9 kg)	9.9 lbs. (4.49 kg)
eFlow102NA8V	8.65 lbs. (3.92 kg)	9.95 lbs. (4.51 kg)
eFlow104NA8V	8.9 lbs. (4.04 kg)	10.2 lbs. (4.63 kg)

Temperature

Operating	0°C to 49°C (32°F to 120°F).
Storage	-20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%

BTU/Hr. (12VDC/24VDC, approx.):

Model	12VDC	24VDC
eFlow4NA8V	25	50
eFlow6NA8V	37	74
eFlow102NA8V	61	N/A
eFlow104NA8V	N/A	123

Accessories

Network Supervision

Altronix model **LINQ2** Network Communication Module provides remote supervision, control and monitoring over LAN/WAN

- Remotely reports accurate power diagnostics
- Controls power and resets devices
- Email and SNMP trap message notifications

