



## eFlowNA Series Power Supply/Chargers with Multi-Output Access Power Controllers

### Description

Altronix eFlowNA series distribute and switch power to access control systems and accessories. They convert a 120VAC, 60Hz input into eight (8) independently controlled 12VDC or 24VDC fuse protected outputs. These power outputs can be converted to dry form “C” contacts. Outputs are activated by an open collector sink or normally open (NO) dry trigger input from an Access Control System, Card Reader, Keypad, Push Button, PIR, etc. Units will route power to a variety of access control hardware devices including: Mag Locks, Electric Strikes, Magnetic Door Holders, etc. Outputs will operate in both Fail-Safe and/or Fail-Secure modes. The FACP Interface enables Emergency Egress, Alarm Monitoring, or may be used to trigger other auxiliary devices. The fire alarm disconnect feature is individually selectable for any or all of the eight (8) outputs.



### Key Features

- Eight (8) independently controlled outputs.
  - Output options:
    - a) Eight (8) Fail-Safe and/or Fail-Secure power outputs.
    - b) Eight (8) form “C” 5A rated relay outputs.
    - c) Any combination of the above.
- Eight (8) auxiliary power outputs (unswitched).
- Output fuses are rated @ 3.5A.
- Filtered and electronically regulated outputs.
- Supervision:
  - AC Fail
  - Battery Fail and Battery Presence
  - Low power shutdown
- Fire Alarm disconnect (latching or non-latching) is individually selectable for any or all of the eight (8) outputs.
- Alarm output relay indicates that FACP input is triggered.
- Fire Alarm disconnect input options:
  - a) Normally open (NO) or normally closed (NC) dry contact input
  - b) Polarity reversal input from FACP signaling circuit
- Built-in charger for sealed lead acid or gel type batteries.
- Instantaneous transfer to stand-by batteries.
- UL Listed in the U.S. and Canada.
- CE Approved.
- Lifetime Warranty / Made in the U.S.A.

### eFlowNA Series Power Supply Configuration Reference Chart

Altronix Model Number	Maximum Supply Current for Main and Aux. Outputs (A)		Fuse Protected Outputs	120VAC 60 Hz Input Current (A)	Current per ACM8 output (A)	Power Supply Board Input Fuse Rating	Power Supply Board Battery Fuse Rating	ACM8 Board Input Fuse Rating	ACM8 Board Output Fuse Rating
	12VDC	24VDC							
eFlow4NA8	3.3A	3.6A	8	3.5A	2.5A	5A/250V	7.5A/32V	10A/250V	2.5A/250V
eFlow6NA8	5.3A	5.6A	8	3.5A	2.5A	5A/250V	10A/32V	10A/250V	2.5A/250V
eFlow102NA8	9.3A	—	8	3.5A	2.5A	5A/250V	15A/32V	10A/250V	2.5A/250V
eFlow104NA8	—	9.6A	8	4.5A	2.5A	6.3A/250V	15A/32V	10A/250V	2.5A/250V

# eFlowNA Series

## Power Supply/Chargers with Multi-Output Access Power Controllers



### Specifications

#### Input

Voltage 120VAC, 60Hz.  
 Fusing Varies, see Reference Chart.

#### Outputs

Voltage 12VDC or 24VDC, see Reference Chart.  
 Current Varies, depending on the model.  
 Protection Fused 3.5A.  
 Auxiliary 2.5A (unswitched).  
 Other Overvoltage protection.  
 Filtered and regulated outputs.

#### Back-up Battery *(not included)*

Capacity 12AH / 12VDC (1 or 2 within enclosure).  
 18AH / 40 AH / 65 AH  
 (requires separate enclosure).  
 Type Sealed lead acid or gel type.  
 Fuse Rating Varies, see Reference Chart.  
 Failover Upon AC loss, instantaneous.

#### Supervision

AC Failure Form "C" contacts.  
 Battery Form "C" contacts.

#### Low DC Power Shutdown

Shuts down DC output terminals if battery voltage drops below 71-73% for 12V units and 70-75% for 24V units (depending on the power supply). Prevents deep battery discharge.

#### Fire Alarm Disconnect

Supervised Latching or non-latching, individually selectable for any or all of the eight (8) outputs.  
 EOL 10K Resistor.

#### Indicators (LED)

Input 120VAC is present.  
 DC Output Powered.  
 Battery Discharged or not connected.  
 Relays Individual LEDs indicate outputs are triggered (relays energized).  
 FACP Indicates FACP disconnect is triggered.

#### Agency Listings

UL:  
 UL294 Access Control System Units.  
 cUL:  
 ULC-S319-05 Electronic Access Control Systems.  
 Class I Equipment;  
 Signal Equipment.  
 CSA C22.2 No.205 Signal Equipment.  
 CSFM California State Fire Marshall Approved.  
 CE European Conformity.

#### Physical and Environmental

##### Dimensions (H x W x D)

15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm).

##### Product Weight / Shipping (approx.)

Model	Product Weight	Shipping Weight
eFlow4NA8	8.65 lbs. (3.92 kg)	9.95 lbs. (4.51 kg)
eFlow6NA8	8.6 lbs. (3.9 kg)	9.9 lbs. (4.49 kg)
eFlow102NA8	8.65 lbs. (3.92 kg)	9.95 lbs. (4.51 kg)
eFlow104NA8	8.9 lbs. (4.04 kg)	10.2 lbs. (4.63 kg)

##### Temperature

Operating 0°C to 49°C (32°F to 120°F).  
 Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%

##### BTU/Hr. (12VDC/24VDC, approx.):

Model	12VDC	24VDC
eFlow4NA8	25	50
eFlow6NA8	37	74
eFlow102NA8	61	N/A
eFlow104NA8	N/A	123

### Accessories

#### Network Supervision

Altronix model **LINQ2** Network Communication Module provides remote supervision, control and monitoring over LAN/WAN

- Remotely reports accurate power diagnostics
- Controls power and resets devices
- Email and SNMP trap message notifications

