

IR623-PoE-2 Series

Product Features

- Long range IR illuminator
- SMT LED technology
- Distances up to 623' (190m)
- Angles 10°, 30°, 60°, 100° & 120°
- 850nm or 940nm Wavelengths
- Low power consumption (36W)
- Long life
- 5 year warranty
- IP67 weatherproof rating
- Built-in photocell IR on/off
- Telemetry input for remote switching
- High Power PoE power

What is IR Illumination?

Active or near infra-red (NIR) illumination is energy which is invisible to the human eye but can be seen by a high quality true day/night camera (IR cut filter removed). The energy from IR illuminators resides just outside the visible red section of the electromagnetic spectrum, above 700nm and below 1000nm.

IR illumination is an ideal source of illumination for security cameras for the following reasons.

- It is invisible to the human eye but visible to black/white and true day/night cameras.
- Avoids the problem of light pollution.
- Longer range than visible light

All Illuminar illuminators provide superior IR lighting for video surveillance systems. They are available with a range of angles to cover different distances and scenes.

Supplied with an IP67 rating, they are vandal proof and can be used indoors and outdoors. The anodized aluminum housing provides protection from the harshest weather conditions.

Professional Illuminators vs Camera Built-in Illuminators

There are many advantages of using separate, professional illuminators versus built-in camera infrared illuminators

- Longer life on the LED's
- No hot spots
- Wider angles
- Longer range
- Avoids attracting insects to obscure camera view

Models

Model Number	Wavelength	Angle	Distance		HOV	
IR623-A10-PoE-2	850nm	10°	623'	190m	108'	33m
IR623-A30-PoE-2	850nm	30°	328'	100m	177'	54m
IR623-A60-PoE-2	850nm	60°	246'	75m	285'	87m
IR623-A100-PoE-2	850nm	100° x 50°	160'	48m	375'	114m
IR623-A120-PoE-2	850nm	120°	131'	40m	456'	139m
IR623-C10-PoE-2	940nm	10°	295'	90m	53'	16m
IR623-C30-PoE-2	940nm	30°	157'	48m	85'	26m
IR623-C60-PoE-2	940nm	60°	118'	36m	138'	42m
IR623-C100-PoE-2	940nm	100° x 50°	75'	23m	180'	55m
IR623-C120-PoE-2	940nm	120°	62'	19m	217'	66m

General

Electronics	High efficiency surface mount high power LED's with advanced current limited integral control circuitry
Number of SMT LED's	12
Construction	Robust high quality aluminum extrusion
Front window	Polycarbonate high transmittance protective (vandal-proof) IR filter
Finish	Black anodized
Power Cable	IP67 rated RJ45 Cat5e
Telemetry Following Contact	Via cable
Pressure Equalization Vent	Prevents thermal expansion & pressure cycling
Photocell	Adjustment via Remote
Illumination	Adjustable via Remote
Operating Temperature	-58° to 140°F (-50° to 60°C)
Weight	3.3lbs (1.5Kg)
Mount	Black powder coated stainless steel wall mount
Dimensions	6.49" x 4.33" x 3.14" (165 x 110 x 80mm)

Electrical

Power over Ethernet (PoE) High Power PoE

Consumption 36W

Wavelength

Standard (A) **850nm** (semi-covert)
Faint red glow visible on the illuminator only (no visible light)

Optional (C) **940nm** (covert)
No visible glow from illuminator – ideal for transportation or high security applications

Certifications

Safety EN60598:2004 Electrical Safety
EN60825-1 Laser Eye Safety

IP IP67 in accordance with EN60529:1992

EMC EN61000, FCC part 15.107
15.108 Class B

WEEE Waste Electrical & Electronic Equipment
European directive 202/96/EC

RoHS Restriction of Hazardous Substances European
directive 202/95/EC